

# Available soon: AvaSpec-Mini-NIR

## Small and Powerful OEM NIR Spectrometer

### AvaSpec-Mini-NIR256-1.7



The latest addition to our CompactLine: the AvaSpec-Mini-NIR!

The AvaSpec-Mini-NIR is a compact NIR spectrometer, based on a combination of our popular AvaSpec-NIR256-1.7 and Mini-series.

This NIR spectrometer might not be as sensitive as our bigger NIR spectrometers, but this loss in sensitivity is greatly compensated by its size and robustness.

Like our other CompactLine spectrometers, this device is only the size of a deck of cards

and USB powered, which makes it easy to integrate into other devices, including but not limited to OEM handheld applications.

This versatile miniature near-infrared spectrometer is well suited for various applications, including food analysis and the recycling industry.

Of course, the AvaSpec-Mini-NIR works seamlessly with our AvaSoft software and the Windows and Linux libraries we have available.

### Technical Data

<b>Optical bench</b>	Symmetrical Czerny-Turner, 75 mm focal length, MK II
<b>Wavelength range</b>	900-1750 nm
<b>Stray light</b>	1%
<b>Sensitivity HS in counts/<math>\mu</math>W per ms</b>	665,000 (integral 1000-1750 nm)
<b>Dynamic range HS</b>	4750:1
<b>Integration time HS</b>	10 $\mu$ s – 300 ms
<b>Signal/noise HS</b>	1900:1
<b>Dark noise HS</b>	14 counts
<b>Sensitivity LN in counts/<math>\mu</math>W per ms</b>	38,000 (integral 1000-1750 nm)
<b>Dynamic range LN</b>	7500:1
<b>Integration time LN</b>	10 $\mu$ s – 5 seconds
<b>Signal/noise LN</b>	5000:1
<b>Dark noise LN</b>	9 counts
<b>Detector</b>	InGaAs array, 256 pixels
<b>AD converter</b>	16-bit, 500 kHz
<b>Interface</b>	USB2.0 (480 Mbps)/pigtailed (50 cm) USB-A
<b>Sample speed with store to RAM</b>	0.53 ms/scan
<b>Data transfer speed</b>	1.2 ms/scan
<b>I/O</b>	5 bidirectional programmable I/O: 1 analog out, 1 analog in, 1 x 5V
<b>Power supply</b>	Default USB power, 500 mA
<b>Dimensions, weight</b>	95 x 68 x 20 mm, 185 g
<b>Temperature range</b>	0-55°C

### Grating selection table for AvaSpec-Mini-NIR

Use	Useable range (nm)	Spectral range (nm)	Lines/mm	Blaze (nm)	Order code
NIR	900-1750	750	200	1550	NIR200-1.6
NIR	900-1495	355-345	400	1210	NIR400-1.2
NIR	1250-1700	340-335	400	1600	NIR400-1.6
NIR	900-1450	225-210	600	1280	NIR600-1.3
NIR	1350-1735	205-185	600	1669	NIR600-1.7

### Resolution table (FWHM in nm) for AvaSpec-Mini-NIR\*

Grating (lines/mm)	Slit size (μm)			
	50	100	200	500
200	6	12	24	50
400	3	6	12	25
600	2	4	4	18

\* Typical values. Small deviations are possible.

### Ordering information

#### AvaSpec-Mini-NIR256-1.7

• Miniature NIR fiber-optic spectrometer, 75 mm focal length, 256 pixel InGaAs detector, USB2 powered interface

*Specify grating, wavelength range and options. Other gratings are possible on request.*

### Options

#### SLIT-XX

• Slit size, please specify XX = 50, 100, 200 or 500 μm

**For non-OEM users, a preconfigured model will be available upon release**